

Intelliprint 9035

Unmatched Fusion of Performance and Productivity



Excellent Speed, Robust Duty Cycle.

The 9035n prints at speeds up to 35 pages per minute with a first page out time of less than 9 seconds. In addition to the rapid printing speeds, the 9035n is capable of handling duty cycles of up to 150,000 pages per month. This kind of performance allows the 9035n to be relied upon in even the most demanding printing environments – situations in which many printers may fail, but where the 9035N fits best!.

Productivity Enhancing Controller Architecture.

The 9035 incorporates the Intelliprint Controller Architecture – a proprietary printing control technology developed by TallyGenicom to provide users with an unmatched fusion of performance and productivity enhancement. Features such as password-protected printing, saved job library and job accounting set the 9035n apart from the competition, and ensure that the 9035 is not just a printer, but a highly flexible document creation tool. In addition to the productivity enhancements offered by the Intelliprint Controller architecture, the 9035n also boasts a class-leading 405 MHz processor, Adobe PostScript 3 and PCL 6 and PCL 5e functionality.

Product Highlights

Less than 9 seconds first page output time.
1200 x 1200 dpi at up to 35 ppm.
Powerful 405 MHz RISC processor processor.
Intellifilter for compatibility with legacy print data streams.
Intelliprint controller.
Adobe PostScript 3, PCL 6, PCL5e.
Optional Duplex Printing.
Duty cycle of 150,000 images per month.
One year on-site warranty.

Available Configuration:

9035N - Ethernet, Parallel, USB, PS3
9035ND - Ethernet, Parallel, USB, PS3, with Duplexer
9035NDT - Ethernet, Parallel, USB, PS3, with Duplexer and Extra Tray
9035N - MICR, Ethernet, Parallel, USB, PS3
9035N - MICR-extended security laser printer, e-net, PS3

Features & Specifications

Print Speed	35 ppm
Print Method	Electro-photographic semiconductor laser with Intelliprint Controller
Processor	MIPS R5000 405 MHz
Resolution	1200 x 1200 dpi
Time To 1st Page	Less than 9 Seconds
Memory	64MB expandable to 256MB (2 slots); Optional 20GB (or higher) hard disk
Standard Connectivity	10/100Base-T Ethernet ; IEEE 1284 parallel; Hi-speed USB v2.0 480 Mb/s. Auto interface switching
Standard Emulation	PostScript 3 (embedded); PCL 6 with PJL, PCL 5e
Print Monitor	TCP/IP, EtherTalk, Rendezvous, SNMP, Printer MIB, e-mail status, and Web-based status and control
Fonts	136 Adobe PostScript fonts; 86 Type 1 PCL
Consumables	Single-element toner cartridge with 17,000 letter (at 5%). New printer comes with 10,000 letter/A4 yield capacity
STD Paper Handling	550-sheet tray; 150-sheet tray
Opt'l Paper Handling	550-sheet feeder tray (up to 2 additional)
Duplexing	Optional
Paper Type	Sheet paper, transparencies
Paper Weight	16 to 58 lbs (60 to 216 g/m ²) in simplex and duplex modes
Paper Size	Letter, executive, legal, folio, A4, A5, A6, B5, index (3x5, tray 1 only), statement; Envelopes: Com10, Monarch, DL, C5 and B5
Paper Output	500-sheet face-down top output; Optional Cassette: 500-sheet offset catch tray
Physical Weight	45 lbs. (20.6 kg)
PhysicalSize	15.9" x 16.6" x 18.3" (404x 422 x 465 mm)
Power Voltage	100/120-127 VAC, 50/60 Hz; Current: 7 amps
Compliance	Energy Star compliant, Ozone-free; UL950, FCC part 15 Class B, ICES 003, CISPR22 Class B, FDA CDRH, cUL, CE, GS, IEC 825,GOST (Russia), SABS (S. Africa), and C-Tick (Australia)
Workload	Up to 150,000 pages per month
Forms Software	Intellifilter; Optional: Intellipress
Drivers	XP, 2003, 95, 98, 2000, Me, NT 4.0; Adobe PostScript and PCL drivers included; Unix and Linux system compatibility
Temperature	Operating: 41° F - 95° F (5° to 35° C)
Humidity	Operating: 15%-85% Non-Condensing
Acoustic	Printing - 49.5 dB(A); Standby - 35 dB(A)
Warranty	One year on-site
Option 1	Add-on Tray - 550 sheet feeder; Duplex Unit; Offset Catch Tray
Option 3	128MB Memory DIMM; 256MB Memory DIMM
Option 3	Intelliprint Barcode Module; Intelliprint Barcode/Real Time Clock Module; Intelliprint Real Time Clock Time Clock
Options 4	Hard disk
Option 5	RS232 interface
Note	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used. Toner saver mode providing up to 40% savings



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2006 TallyGenicom, L.P.

4500 Daly Drive, Suite 100
Chantilly, VA 20151
T 800.436.4266
www.tallygenicom.com